

---

**bravado***core*

***Release 4.8.0***

**Jun 14, 2018**



---

## Contents

---

<b>1</b>	<b>Configuration</b>	<b>3</b>
<b>2</b>	<b>Python Models</b>	<b>5</b>
<b>3</b>	<b>User-Defined Formats</b>	<b>9</b>
<b>4</b>	<b>Changelog</b>	<b>13</b>
<b>5</b>	<b>Indices and tables</b>	<b>19</b>



bravado\_core is a Python library that implements the Swagger 2.0 Specification.

Client and servers alike can use bravado\_core to implement these features:

- Swagger Schema ingestion and validation
- Validation and marshalling of requests and responses
- Validation and marshalling of user-defined Swagger formats
- Modelling Swagger *#/definitions* as Python classes or dicts

For example:

- [bravado](#) uses bravado-core to implement a fully functional Swagger client.
- [pyramid\\_swagger](#) uses bravado-core to seamlessly add Swagger support to Pyramid webapps.

Contents:



# CHAPTER 1

---

## Configuration

---

All configuration is stored in a dict.

```
from bravado_core.spec import Spec

spec_dict = json.loads(open('swagger.json', 'r').read())

config = {
    'validate_requests': False,
    'use_models': False,
}

swagger_spec = Spec.from_dict(spec_dict, config=config)
```

Config key	Type	Default	Description
<i>validate_swagger_spec</i>	boolean	True	Validate the Swagger spec against the Swagger 2.0 Specification.
<i>validate_requests</i>	boolean	True	On the client side, validates outgoing requests. On the server side, validates incoming requests.
<i>validate_responses</i>	boolean	True	On the client side, validates incoming responses. On the server side, validates outgoing responses.
<i>use_models</i>	boolean	True	Use python classes to represent models instead of dicts. See <a href="#">Python Models</a> .
<i>formats</i>	list of SwaggerFormat	[]	List of user-defined formats to support. See <a href="#">User-Defined Formats</a> .
<i>include_missing_properties</i>	boolean	True	Create properties with the value <code>None</code> if they were not submitted during object unmarshalling



## CHAPTER 2

---

### Python Models

---

Models in a Swagger spec are usually defined under the path `#/definitions`.

A model can refer to a primitive type or a container type such as a list or a dict. In dict form, there is an opportunity to make the interface to access the properties of a model a little more straight forward.

Consider the following:

```
{
  "definitions": {
    "Pet": {
      "type": "object",
      "required": ["name"],
      "properties": {
        "name": {"type": "string"},
        "age": {"type": "integer"},
        "breed": {"type": "string"}
      }
    }
  }
}
```

In python, this model easily maps to a dict:

```
pet = {
    "name": "Sumi",
    "age": 12,
    "breed": None,
}

print pet['name']

if pet['age'] < 1:
    print 'What a cute puppy!'
```

(continues on next page)

(continued from previous page)

```
if pet['breed'] is None:
    pet['breed'] = 'mutt'
```

However, if the model is implemented as a Python type, dotted access to properties becomes a reality:

```
from bravado_core.spec import Spec

spec = Spec.from_dict(...)
Pet = spec.definitions['Pet']
pet = Pet(name='Sumi', age=12)

print pet.name

if pet.age < 1:
    print 'What a cute puppy!'

if pet.breed is None:
    pet.breed = 'mutt'
```

## 2.1 Configuring Models as Python Types

bravado-core supports models as both dicts and python types.

The feature to use python types for models is enabled by default. You can always disable it if necessary.

```
from bravado_core.spec import Spec
swagger_dict = {...}
spec = Spec.from_dict(swagger_dict, config={'use_models': False})
```

## 2.2 Allowing null values for properties

Typically, bravado-core will complain during validation if it encounters fields with `null` values. This can be problematic, especially when you're adding Swagger support to pre-existing APIs. In that case, declare your model properties as `x-nullable`:

```
{
  "Pet": {
    "type": "object",
    "properties": {
      "breed": {
        "type": "string",
        "x-nullable": true
      }
    }
  }
}
```

`x-nullable` is an extension to the Swagger 2.0 spec. A nullable attribute is being [considered](#) for the next major version of Swagger.

## 2.3 Model Discovery

Keep in mind that bravado-core has to do some extra legwork to figure out which parts of your spec represent Swagger models and which parts don't to make this feature work automatically. With a single-file Swagger spec, this is pretty straight forward - everything under `#/definitions` is a model. However, with more complicated specs that span multiple files and use external refs, it becomes a bit more involved. For this reason, the discovery process for models is best effort with a fallback to explicit annotations as follows:

1. Search for refs that refer to `#/definitions` in local scope
2. Search for refs that refer to external definitions with pattern `<filename>#/definitions/<model name>`.

*swagger.json*

```
{
  "paths": {
    "/pet": {
      "get": {
        "responses": {
          "200": {
            "description": "A pet",
            "schema": {
              "$ref": "another_file.json#/definitions/Pet"
            }
          }
        }
      }
    }
  }
}
```

*another\_file.json*

```
{
  "definitions": {
    "Pet": {
      ...
    }
  }
}
```

3. Search for the `"x-model": "<model name>"` annotation to identify models that can't be found via method 1. or 2.

*swagger.json*

```
{
  "paths": {
    "/pet": {
      "get": {
        "responses": {
          "200": {
            "description": "A pet",
            "schema": {
              "$ref": "https://my.company.com/definitions/models.
↪json#/models/Pet"
            }
          }
        }
      }
    }
  }
}
```

(continues on next page)

(continued from previous page)

```
}
  }
  }
}
```

*models.json* (served up via <https://my.company.com/definitions/models.json>)

```
{
  "models": {
    "Pet": {
      "x-model": "Pet"
      ...
    }
  }
}
```

---

## User-Defined Formats

---

Primitive types in Swagger support an optional modifier property `format` as explained in detail in the [Swagger Specification](#). With this feature, you can define your own domain specific formats and have validation and marshalling to/from python/json handled transparently.

### 3.1 Creating a user-defined format

This is best explained with a simple example. Let's create a user-defined format for [CIDR notation](#).

In a Swagger spec, the schema-object for a CIDR would resemble:

```
{
  "type": "string",
  "format": "cidr",
  "description": "IPv4 CIDR"
}
```

In python, we'd like CIDRs to automatically be converted to a CIDR object that makes them easy to work with.

```
class CIDR(object):
    def __init__(self, cidr):
        """
        :param cidr: CIDR in string form.
        """
        self.cidr = cidr

    def overlaps(self, other_cidr):
        """Return true if other_cidr overlaps with this cidr"""
        ...

    def subnet_mask(self):
        """Return the subnet mask of this cidr"""
        ...
```

(continues on next page)

(continued from previous page)

...

We would also like CIDRs to be validated by bravado-core whenever they are part of a HTTP request or response.

Create a `bravado_core.formatter.SwaggerFormat` to define the CIDR format:

```
from bravado_core.formatter import SwaggerFormat

def validate_cidr(cidr_string):
    if '/' not in cidr_string:
        raise SwaggerValidationError('CIDR {0} is invalid'.format(cidr_string))

cidr_format = SwaggerFormat(
    # name of the format as used in the Swagger spec
    format='cidr',

    # Callable to convert a python CIDR object to a string
    to_wire=lambda cidr_object: cidr_object.cidr,

    # Callable to convert a string to a python CIDR object
    to_python=lambda cidr_string: CIDR(cidr_string),

    # Callable to validate the cidr in string form
    validate=validate_cidr
)
```

## 3.2 Configuring user-defined formats

Now that we have a `cidr_format`, just pass it to a `Spec` as part of the `config` parameter on `Spec` creation.

```
from bravado_core.spec import Spec

spec_dict = json.loads(open('swagger.json', 'r').read())
config = {
    'validate_responses': True,
    'validate_requests': True,
    'formats': [cidr_format],
}
spec = Spec.from_dict(spec_dict, config=config)
```

All validation and processing of HTTP requests and responses will now use the configured format where appropriate.

## 3.3 Putting it all together

A simple example of passing a CIDR object to a request and getting a list of CIDR objects back from the response.

```
{
  "paths": {
    "/get_overlapping_cidrs": {
      "get": {
        "parameters": [
```

(continues on next page)

(continued from previous page)

```

        {
            "name": "cidr",
            "in": "query",
            "type": "string",
            "format": "cidr"
        }
    ],
    "responses": {
        "200": {
            "description": "List of overlapping cidrs",
            "schema": {
                "type": "array",
                "items": {
                    "type": "string",
                    "format": "cidr"
                }
            }
        }
    }
}

```

```

from bravado_core.spec import Spec
from bravado_core.response import unmarshal_response
from bravado_core.param import marshal_param

# Retrieve the swagger spec from the server and json.load() it
spec_dict = ...

# Create cidr_format add it to the config dict
config = ...

# Create a bravado_core.spec.Spec
swagger_spec = Spec.from_dict(spec_dict, config=config)

# Get the operation to invoke
op = swagger_spec.get_op_for_request('GET', '/get_overlapping_cidrs')

# Get the Param that represents the cidr query parameter
cidr_param = op.params.get('cidr')

# Create a CIDR object - to_wire() will be called on this during marshalling
cidr_object = CIDR('192.168.1.1/24')
request_dict = {}

# Marshal the cidr_object into the request_dict.
marshal_param(cidr_param, cidr_object, request_dict)

# Lots of hand-wavey stuff here - use whatever http client you have to
# send the request and receive a response
response = http_client.send(request_dict)

# Extract the list of cidrs
cidrs = unmarshal_response(response)

```

(continues on next page)

(continued from previous page)

```
# Verify cidrs are CIDR objects and not strings
for cidr in cidrs:
    assert type(cidr) == CIDR
```



### 4.1 4.8.0 (2017-07-15)

- Add support for Swagger spec flattening - PR #177.
- Fix handling of API calls that return non-JSON content (specifically text content) - PR #175. Thanks mostrows2 for your contribution!
- Fix error message text when trying to unmarshal an invalid model - PR #179.

### 4.2 4.7.3 (2017-05-05)

- Fix support for object composition (allof) for data passed in the request body - PR #167. Thanks Zi Li for your contribution!
- Return the default value for an optional field missing in the response - PR #171.

### 4.3 4.7.2 (2017-03-23)

- Fix unmarshalling of null values for properties with no spec - Issue #163, PR #165.

### 4.4 4.7.1 (2017-03-22)

- Fix backward-incompatible Model API change which renames all model methods to have a single underscore in front of them. A deprecation warning has been added - Issue #160, PR #161. Thanks Adam Ever-Hadani for the contribution!

## 4.5 4.7.0 (2017-03-21)

- Added support for nullable fields in the format validator - PR #143. Thanks Adam Ever-Hadani
- Add include\_missing\_properties configuration - PR #152
- Consider default when unmarshalling - PR #154
- Add discriminator support - PR #128, #159. Thanks Michael Jared Lumpe for your contribution
- Make sure pre-commit hooks are installed and run when running tests - PR #155, #158

## 4.6 4.6.1 (2017-02-15)

- Fix unmarshalling empty array types - PR #148
- Removed support for Python 2.6 - PR #147

## 4.7 4.6.0 (2016-11-28)

- Security Requirement validation (for ApiKey) - PR #124
- Allow self as name for model property, adds new “create” alternate model constructor - Issue #125, PR #126.
- Allow overriding of security specs - PR #121
- Adds minimal support for responses with text/\* content\_type.

## 4.8 4.5.1 (2016-09-27)

- Add marshal and unmarshal methods to models - PR #113, #120.

## 4.9 4.5.0 (2016-09-12)

- Support for model composition through the allOf property - Issue #7, PR #63, #110. Thanks David Bartle for the initial contribution!
- Fix issue with header parameter values being non-string types - PR #115.

## 4.10 4.4.0 (2016-08-26)

- Adds support for security scheme definitions, mostly focusing on the “apiKey” type - PR #112.

## 4.11 4.3.2 (2016-08-17)

- Fixes around unmarshalling, x-nullable and required behavior - Issue #108, PR #109. Big thanks to Zachary Roadhouse for the report and pull request!

- Fix `AttributeError` when trying to unmarshal a required array param that's not present - PR #111.

## **4.12 4.3.1 (2016-08-09)**

- Check if a parameter is bool-type before assuming it's a string - PR #107. Thanks to Nick DiRienzo for the pull request!

## **4.13 4.3.0 (2016-08-04)**

- Add support for `x-nullable` - Issue #47, PR #64 and #103. Thanks to Andreas Hug for the pull request!
- Fix support for vendor extensions at the path level - PR #95, #106. Thanks to Mikołaj Siedlarek for the initial pull request!

## **4.14 4.2.5 (2016-07-27)**

- Add `basepython python2.7` for `flake8`, `docs`, and `coverage tox` commands

## **4.15 4.2.4 (2016-07-26)**

- `coverage v4.2` was incompatible and was breaking the build. Added `--append` for the fix.

## **4.16 4.2.3 (2016-07-26)**

- Accept tuples as a type list as well.

## **4.17 4.2.2 (2016-04-01)**

- Fix marshalling of an optional array query parameter when not passed in the service call - PR #87

## **4.18 4.2.1 (2016-03-23)**

- Fix optional enums in request params - Issue #77
- Fix resolving refs during validation - Issue #82

## **4.19 4.2.0 (2016-03-10)**

- More robust handling of `operationId` which contains non-standard chars - PR #76
- Provide a client ingestible version of `spec_dict` with `x-scope` metadata removed. Accessible as `Spec.client_spec_dict` - Issue #78

## 4.20 4.1.0 (2016-03-01)

- Better handling of query parameters that don't have a value - Issue #68
- Allow marshalling of objects which are subclasses of dict - PR #61
- Fix boolean query params to support case-insensitive true/false and 0/1 - Issue #70
- Support for Swagger specs in yaml format - Issue #42
- Fix validation of server side request parameters when collectionFormat=multi and item type is not string - Issue #66
- Fix unmarshaling of server side request parameters when collectionFormat=multi and cardinality is one - PR #75

## 4.21 4.0.1 (2016-01-11)

- Fix unmarshalling of an optional array query parameter when not passed in the query string.

## 4.22 4.0.0 (2015-11-17)

- Support for recursive \$refs - Issue #35
- Requires swagger-spec-validator 2.0.1
- Unqualified \$refs no longer supported. Bad: {"\$ref": "User"} Good: {"\$ref": "#/definitions/User"}
- Automatic tagging of models is only supported in the root swagger spec file. If you have models defined in \$ref targets that are in other files, you must manually tag them with 'x-model' for them to be available as python types. See [Model Discovery](#) for more info.

## 4.23 3.1.1 (2015-10-19)

- Fix the creation of operations that contain shared parameters for a given endpoint.

## 4.24 3.1.0 (2015-10-19)

- Added http headers to `bravado_core.response.IncomingResponse`.

## 4.25 3.0.2 (2015-10-12)

- Added docs on how to use [user-defined formats](#).
- Added docs on how to [configure](#) bravado-core.
- *formats* added as a config option

## 4.26 3.0.1 (2015-10-09)

- Automatically tag models in external \$refs - Issue #45 - see [Model Discovery](#) for more info.

## 4.27 3.0.0 (2015-10-07)

- User-defined formats are now scoped to a Swagger spec - Issue #50 (this is a non-backwards compatible change)
- Deprecated `bravado_core.request.RequestLike` and renamed to `bravado_core.request.IncomingRequest`
- Added *make docs* target and updated docs (still needs a lot of work though)

## 4.28 2.4.1 (2015-09-30)

- Fixed validation of user-defined formats - Issue #48

## 4.29 2.4.0 (2015-08-13)

- Support relative '\$ref' external references in swagger.json
- Fix dereferencing of jsonref when given in a list

## 4.30 2.3.0 (2015-08-10)

- Raise `MatchingResponseNotFound` instead of `SwaggerMappingError` when a response can't be matched to the Swagger schema.

## 4.31 2.2.0 (2015-08-06)

- Add reason to `IncomingResponse`

## 4.32 2.1.0 (2015-07-17)

- Handle user defined formats for serialization and validation.

## 4.33 2.0.0 (2015-07-13)

- Move http invocation to `bravado`
- Fix unicode in model docstrings
- Require `swagger-spec-validator` 1.0.12 to pick up bug fixes

## 4.34 1.1.0 (2015-06-25)

- Better unicode support
- Python 3 support

## 4.35 1.0.0-rc2 (2015-06-01)

- Fixed file uploads when marshaling a request
- Renamed ResponseLike to IncomingResponse
- Fixed repr of a model when it has an attr with a unicode value

## 4.36 1.0.0-rc1 (2015-05-26)

- Use basePath when matching an operation to a request
- Refactored exception hierarchy
- Added use\_models config option

## 4.37 0.1.0 (2015-05-13)

- Initial release

## CHAPTER 5

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`